


STRAINER

Cast iron and threaded stainless steel

Art. 707.0005 Cast iron NP 20



Art. 707.0005



Sec.Art. 707.0005

Execution: cast iron body and bonnet GG-25 - stainless steel filtering wire - holes $\varnothing 1.2$ mm with 7.2 holes/cm² - stainless steel gasket - threaded ends BSPT type conical.

Diameters: 3/8" ÷ 2"

Max pressure 20 bar


Max temperature 220°C

Employments: heating plants - steam.

Sizes

\bar{R}	L	H	Is	ds
3/8"	65	48	32	18
1/2"	75	60	35	20
3/4"	90	75	50	25
1"	110	85	60	32
1 1/2"	135	95	70	40
1 1/4"	145	105	75	45
2"	170	115	90	56

Art. 066.2016 Stainless steel NP 64



Art. 066.2016

Execution: stainless steel body and cap ASTM A351Gr. CF8M (AISI 316) - nodular graphite cap gasket - stainless steel filter AISI 316 - filtering holes diameter 0.8mm.

Diameters: 3/8" ÷ 2"

Max pressure 66,5 bar (120°C)

Max pressure 52 bar (268°C)

Max pressure 45 bar (400°C)

Max temperature 400°C


Hydraulic test (cold) 125 bar

Employments: steam - condensate - compressed air - hot, cold or superheated water - oils.

On request: filtering sieve 100 mesh.

Sizes

\bar{R}	L	H	Y	Filtering air cm ²
3/8"	69	55	26	25
1/2"	76	55	32	25
3/4"	88	65	38	42
1"	106	78	46	71
1 1/2"	133	103	56	135
1 1/4"	146	115	62	151
2"	172	140	76	251



Sec.Art. 066.2016

