



Art. 008.6083 NP 25 UNI 6083/67

Art. 008.6084 NP 40 UNI 6084/67

Execution: ASTM A105 steel - inside and on the contact surface turned - drilled as table - phonometric lines - overlap welding.

Diameters: ND 10 ÷ ND 400

On request: raised face according to UNI 2229 - outside turned - FE 410 construction.

Dimensions and weights

ND	FLANGE			DRILLING			Approx. weight Kg.
	Outside diameter D	Inside diameter d DIN	ISO	Thickness b	Holes n°	Diameter f	

UNI 6083/67 NP 25

FROM ND 10 TO ND 150 USE FLANGES NP 40 UNI 6084/67

200	360	221	221	32	12	25	360	14.300
250	425	269	275	36	12	30	425	20.900
300	485	326	326	40	16	30	485	28.300
350	555	370.5	358	44	16	33	555	44.100
400	620	422	409	48	16	36	620	58.100

UNI 6084/67 NP 40

10	90	14	18	14	4	14	60	0.600
15	95	21	22	14	4	14	65	0.670
20	105	26	28	16	4	14	75	0.940
25	115	31	34	16	4	14	85	1.110
32	140	39	43	18	4	18	100	1.830
40	150	45	49	18	4	18	110	2.090
50	165	58	62	20	4	18	125	2.730
65	185	77	77	24	8	18	145	3.800
80	200	90	90	26	8	18	160	4.700
100	235	109	116	26	8	22	190	6.090
125	270	135	141	28	8	25	220	8.220
150	300	161	170	30	8	25	250	10.300
175	350	196	196	34	12	30	295	15.400
200	375	221	221	36	12	30	320	18.-
250	450	269	275	44	12	33	385	30.900
300	515	326	326	48	16	33	450	41.900
350	580	371	358	54	16	36	510	62.400
400	660	422	409	60	16	39	585	90.300