

REDUCTION

ISO seamless concentric and eccentric



Art. 036.0956 Concentric

Art. 036.0957 Eccentric


Execution: produced from seamless steel pipes - manufacturing, execution and tolerances according to DIN 2616-DIN 2609 - the reductions meet UNI/ISO 3419 requirements.

Dimensions


Big \check{R}		Small \check{r}		H mm	Tolerances H mm	Theoretic weight Kg
\check{R} D.	Thickness mm	\check{r} d	Thickness mm			
26.9	2.3	21.3	2.0	38	± 2.5	0.080
33.7	2.6	21.3	2.0	50	± 2.5	0.090
33.7	2.6	26.9	2.3	50	± 2.5	0.090
42.4	2.6	21.3	2.0	50	± 2.5	0.120
42.4	2.6	26.9	2.3	50	± 2.5	0.130
42.4	2.6	33.7	2.6	50	± 2.5	0.140
48.3	2.6	26.9	2.3	64	± 2.5	0.190
48.3	2.6	33.7	2.6	64	± 2.5	0.200
48.3	2.6	42.4	2.6	64	± 2.5	0.200
60.3	2.9	26.9	2.3	76	± 2.5	0.300
60.3	2.9	33.7	2.6	76	± 2.5	0.310
60.3	2.9	42.4	2.6	76	± 2.5	0.320
60.3	2.9	48.3	2.6	76	± 2.5	0.330
76.1	2.9	33.7	2.6	90	± 2.5	0.400
76.1	2.9	42.4	2.6	90	± 2.5	0.470
76.1	2.9	48.3	2.6	90	± 2.5	0.480
76.1	2.9	60.3	2.9	90	± 2.5	0.490
88.9	3.2	42.4	2.6	90	± 3	0.550
88.9	3.2	48.3	2.6	90	± 3	0.610
88.9	3.2	60.3	2.9	90	± 3	0.620
88.9	3.2	76.1	2.9	90	± 3	0.630
114.3	3.6	48.3	2.6	100	± 3	0.850
114.3	3.6	60.3	2.9	100	± 3	0.980
114.3	3.6	76.1	2.9	100	± 3	1.000
114.3	3.6	88.9	3.2	100	± 3	1.020
139.7	4.0	60.3	2.9	127	± 3.5	1.600
139.7	4.0	76.1	2.9	127	± 3.5	1.700
139.7	4.0	88.9	3.2	127	± 3.5	1.740
139.7	4.0	114.3	3.6	127	± 3.5	1.760
168.3	4.5	76.1	2.9	140	± 3.5	2.600
168.3	4.5	88.9	3.2	140	± 3.5	2.700
168.3	4.5	114.3	3.6	140	± 3.5	2.820
168.3	4.5	139.7	4.0	140	± 3.5	2.940
219.1	6.3	114.3	3.6	152	± 3.5	5.030
219.1	6.3	139.7	4.0	152	± 3.5	5.120
219.1	6.3	168.3	4.5	152	± 3.5	5.180
273	6.3	114.3	3.6	178	± 4	7.000
273	6.3	139.7	4.0	178	± 4	7.200
273	6.3	168.3	4.5	178	± 4	7.400
273	6.3	219.1	6.3	178	± 4	7.550
323.9	7.1	168.3	4.5	203	± 5	11.00
323.9	7.1	219.1	6.3	203	± 5	11.10
323.9	7.1	273	6.3	203	± 5	11.20



Art. 036.0956



Sec.art. 036.0956



Sec.art. 036.0957

